24/Seven® Solid GR - Interlocking Rubber Floor Tiles 3′ x 3′

Group 570-GR



24/Seven is a collection of high performance, 3’x3’ (91 x 91 cm), interconnecting rubber anti-fatigue mats. These resilient modular mats are 5/8” (16mm) thick and tough enough to handle 24/7 shift operations, but supple enough to provide cushioned support where it’s needed. Because of its modularity, 24/Seven can be positioned to cover large flooring areas, single workstations and assembly lines. For extra safety attach optional 3 x 39 in. (8 x 99 cm) beveled yellow safety edges. Check out our NEW & IMPROVED 24/SEVEN LockSafe!

- Available in 3 different rubber compounds based on environmental exposures:
- GR - for water or dry debris
- CFR - for mineral oil-based fluids
- NBR - for petroleum-based fluids
- Hidden interlocks
- Choice of solid or drainage styles
- Choose GRITSHIELD for increased traction
- Custom widths or unique configurations are available in 12″ (30 cm) increments
- Overall thickness 5/8″ (16 mm)

Categories & Applications	Anti-Fatigue Flooring
Suitable Environment	Dry floors with an occasional spill. Avoid constant pooling fluids. Clean with a neutral PH cleaner., Wet Area, Slippery
Customization Options	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Solid
Material	Grease Resistant Natural Rubber (GR)
Recycled	>50%
Warranty	Limited Lifetime

info@sarax.com.mx
818 333 3335
811 910 1772

www.sarax.com.mx

Pablo Moncayo N° 147, Colinas de San Jerónimo, Monterrey, Nuevo León

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 2% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .78 / Wet COF = .68
Compression Deflection	ASTM D575 - 25.3 psi @ 15% =.1" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

info@sarax.com.mx
818 333 3335
811 910 1772

Pablo Moncayo N° 147, Colinas de San Jerónimo, Monterrey, Nuevo León