Diamond-Plate Nitricell SpongeCote with Stay- Put Finish Mat - Black with Yellow Borders

Group 815BYL



Wearwell continues to set the industry benchmark in matting, flooring, and facility solutions. Stay-Put, a special finish that prevents mats from sliding in use, is no exception. Whether you are working on dusty concrete or slick epoxy, mats should not slide around. Stay-Put Finish finally solves this decades old problem. Diamond-Plate Nitricell SpongeCote with Stay-Put Finish has taken our most premium products to the next level. This new "Gold Standard" has a tough diamond surface, extra-thick ergonomic build, and keeps mats safely in place.

- Stop sliding mats with Stay-Put Finish
- New 'Gold Standard' of matting
- Thick, premium ergonomics
- Unique polymer is permanently tacky and easy to remove
- Designed to prevent slips, trips, and falls
- Works right out of the box!
- Abrasion and chemical resistant surface
- Overall thickness 9/16" (14 mm)
- Need a different size? 1' incremental lengths are available! Simply give us a shout out!

Categories & Applications	Anti-Fatigue Matting.
Suitable Environment	Dry floors with an occasional spill. Avoid constant pooling fluids. Clean with a neutral PH cleaner.
Customization Options	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Solid
Material	PVC Surface With Nitrile Infused Sponge
Recycled	>50%
Warranty	Limited Lifetime

info@sarax.com.mx
818 333 3335
811 910 1772

www.sarax.com.mx

Pablo Moncayo N° 147, Colinas de San Jerónimo, Monterrey, Nuevo León

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .68 / Wet: COF = .17
Compression Deflection	7.1 psi @ 25% = .15" distance compressed
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

info@sarax.com.mx
818 333 3335
811 910 1772
www.sarax.com.mx
Pablo Moncayo N° 147, Colinas de San Jerónimo, Monterrey, Nuevo León