

TECHNICAL DATASHEET



General Information:

D-Wipe® Towels are saturated with a gentle solution that neutralizes the static charges of lead and metal dust while lifting and binding them to the soft fabric for quick removal from the skin without smearing.

- Removes lead, chromium, mercury, arsenic, cadmium, nickel, silver, zinc and most other metals.
- No rinsing necessary.

Tips for Cleaning:

- Wipe hands, arms and face thoroughly using the entire surface of the towel.
- Discard after single use.

Parameter

Specification

Appearance and Odor:	White applicator towel saturated with clear liquid. Citrus odor
Liquid pH:	4.5 – 5.5
VOC content:	8 % max.

Handling: Keep out of reach of children except under adult supervision. Keep container tightly closed in a cool, dry and well-ventilated place. Store in suitable labeled containers.

Avoid contact with eyes. For external use only.

Storage: Storage between 40 – 100 °F (4 - 38 °C), out of direct sunlight and away from extreme heat. Store away from sources of ignition.

Shelf Life: 30 month from the date of manufacture. PAO: 3 month

Ordering Information:

Product Item#	Towel size	Towels/ canister	Canister/Case	Case Weight (Lbs)
WT-040	8" x 6"	40 towels	12	9
WT-070	10" x 8"	70 towels.	6	15
WT-150	6.5" x 6	150 towels.	8	20
WT-325	8" x 6"	325 towels.	2	11
WT-101	7" x 6"	Individually wrapped	100	2
WT-501	7" x 6"		500	10

The information contained herein is being furnished for informational purposes only, upon the express condition that the User makes its own assessment of the appropriate use of such information. While the information contained herein is believed to be reliable, no representations, guarantees or warranties of any kind are made as to its accuracy, suitability for a particular application or the results to be obtained here from. ESCA Tech, Inc. ("ESCA") cannot guarantee how any products associated with this information will perform in combination with other substances or in the User's process. Due to variations in methods, conditions and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of the information or products for the applications disclosed. ESCA shall not be liable and the User assumes all risk and responsibility for any use or handling of any material beyond ESCA's direct control. ESCA MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. It is the User's sole responsibility to determine if there are any issues relating to patent infringement of any component or combination of components relating to the supplied information. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner.